



Our FACADO-series bollard lights feature IP65 degree of protection for excellent weather resistance. Choose between an opal diffuser or a transparent diffuser with smoked glass to suit your requirements. The series is available in two different sizes (650 mm/1,000 mm) and features an E27 socket for replaceable lamps. The newly designed lamp head provides significantly improved illumination. The FACADO light is made of high-quality, high-pressure die-cast aluminium and is available in dark grey or rust and in square or round designs.

The IP67 connection box features a double M20 cable gland suitable for buried cables in sizes 3x1.5 mm<sup>2</sup>, 5x1.5 mm<sup>2</sup> or 3x2.5 mm<sup>2</sup>, and more.

**Special features**

- IP65 weather resistance
- IP67 connection box suitable for buried cables 3x1.5 mm<sup>2</sup>/5x1.5 mm<sup>2</sup>/3x2.5 mm<sup>2</sup>, and more
- newly designed lamp head for improved illumination
- available with an opal diffuser or a transparent diffuser with smoked glass
- ideal for e.g. ST64 bulbs and A60/70 bulbs

<b>Housing Material</b>	Aluminium, Polycarbonate
<b>Housing Color</b>	Dark grey
<b>Housing Surface</b>	Matt
<b>Material of Lens</b>	Polycarbonate - PC
<b>Colour of Lens</b>	White
<b>Surface Structure of Lens</b>	Transparent
<b>Protection Class</b>	Protection class I/protective grounding
<b>max. Power</b>	1x max. 20 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Socket Description</b>	E27
<b>Illuminant Design</b>	A60, A70, ST64
<b>Socket Quantity</b>	1
<b>Connection Type</b>	Connectionbox
<b>Dimmable</b>	Yes
<b>Control</b>	Dimmable via optional light source
<b>Motion Detector</b>	No
<b>Execution</b>	Without lamp
<b>Light Exit Surfaces</b>	5
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top, Side
<b>Height</b>	1000 mm
<b>Diameter</b>	108 mm
<b>Product weight</b>	2600 g
<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 65