

**Artikel Nr.: 733019**

Stehleuchte, Zilly II, Kupfer, 220-240V AC/50-60Hz, 2x max. 35,00 W



**Technische Daten**

**Charakteristik**

<b>Material</b>	Edelstahl
<b>Farbe</b>	Kupfer
<b>Optik</b>	
<b>im Lieferumfang</b>	3x Schrauben mit Dübel



**Elektrische Daten**

<b>Leistung</b>	2x max. 35,00 W
<b>Eingangsspannung</b>	220-240V AC/50-60Hz
<b>Eingangsstrom</b>	
<b>Fassung / Sockel</b>	GU10
<b>Anzahl Sockel</b>	2
<b>Netzgerät</b>	
<b>Anschlussmöglichkeit</b>	Klemme
<b>Schutzklasse I, II, III</b>	I



**Artikel Nr.: 733019**

Stehleuchte, Zilly II, Kupfer, 220-240V AC/50-60Hz, 2x max. 35,00 W



**Lichtrichtung**


<b>Dreh- und Schwenkbereich</b>	drehbar
<b>Neigungswinkel</b>	140°
<b>Abstrahlverhalten</b>	2 Side
<b>Reflektor / Linse</b>	



**Abmessungen und Gewicht**

<b>Länge</b>	
<b>Breite</b>	232 mm
<b>Höhe</b>	1000 mm
<b>Durchmesser</b>	60 mm
<b>Gewicht</b>	1400 g

**Grenzwerte**

<b>Betriebstemperatur</b>	-20°C - +40°C
<b>Lagertemperatur</b>	-10°C - +60°C
<b>IP - Schutzart</b>	IP44



<b>EEL</b>	Die Leuchte ist geeignet für Leuchtmittel der Energieeffizienzklassen A++ bis E
<b>IP44</b>	Schutz gegen das Eindringen von Fremdkörper > 1 mm. Geschützt gegen Spritzwasser.
	Leuchte der Schutzklasse I bei der der Schutz gegen elektrischen Schlag nicht allein auf der Basisisolierung beruht, sondern die eine zusätzliche Sicherheitsvorkehrung derart enthält, dass berührbare leitfähige Teile mit Mitteln zum Anschluss an den Schutzleiter der festen Installation ausgerüstet sind, so dass im Fehlerfall der Basisisolierung berührbare leitfähige Teile nicht aktiv werden können.
	Aufgrund des komplexen Herstellungsprozesses von LED stellen die angegebenen Werte nur rein statistische Größen dar und müssen nicht zwingend den tatsächlichen Parametern jedes einzelnen LED-Moduls entsprechen, sondern können von den typischen Werten abweichen.

**Article no.: 733019**

Floor lamp, Zilly II, copper, 220-240V AC/50-60Hz, 2x max. 35,00 W

**Technical Data****General Characteristics**

<b>Material</b>	stainless steel
<b>Colour</b>	copper
<b>Optics</b>	
<b>included in delivery</b>	3x screws with dowels

**Electrical Characteristics**

<b>Power</b>	2x max. 35,00 W
<b>Input Voltage</b>	220-240V AC/50-60Hz
<b>Input current</b>	
<b>Base (standard designation)</b>	GU10
<b>Number of Bases</b>	2
<b>Power supply unit</b>	
<b>Connection possibility</b>	clamp
<b>Protection class I, II, III</b>	I



**Article no.: 733019**

Floor lamp, Zilly II, copper, 220-240V AC/50-60Hz, 2x max. 35,00 W



**Light Direction**


Rotating and tilting range	rotatable
Angle of inclination	140°
Radiation direction	2 Side
Reflector / lense	



**Dimensions & Weight**

Length	
Width	232 mm
Height	1000 mm
Diameter	60 mm
Product Weight	1400 g

**Absolute maximum ratings**

Working temperature	-20°C - +40°C
Storage temperature	-10°C - +60°C
IP - Code	IP44



EEI	The luminaire is suitable for lamps of energy efficiency classes A++ to E.
IP44	Protection against penetration of foreign objects > 1 mm. Protection against penetration of splashing water.
	Lightings of Protection Class I in which the protection against electric shock is not based solely on isolation, but an additional safety measure contains such a way that accessible conductive parts are equipped with means for connection to the protective conductor of the fixed installation, so that in case of failure of the basic insulation exposed conductive parts cannot be active.
	Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.