

Artikel Nr.: 862094

Netzgerät, LONG-FLAT, CV, LT-60-24












IP20 CE

Elektrische Daten

Betriebsart	spannungskonstant	Eingangsspannung	220-240V AC/50-60Hz
Leistung	60,00 W	Leistungsfaktor	0,95
Ausgangsspannung	24V DC	Anschlußmöglichkeit	Klemme
Ausgangsstrom	0-2500 mA		


Produkteigenschaften

	Schutzklasse II		Überspannungsschutz
SELV	Schutzkleinspannung		Lampenbetriebsgerät 110
	Kurzschlußfest		Möbeleinbau geeignet
	Überlastschutz	ErP	Standby-Stromverbrauch < 0,5 W
	Übertemperaturschutz	LVD	Sicherheit nach EN 61347
	Sicherheitstrafo	EMC	Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
	nicht dimmbar	EMC	Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

Artikel Nr.: 862094

Netzgerät, LONG-FLAT, CV, LT-60-24

**Abmessungen und Gewicht****Grenzwerte**

Länge	305,00 mm	Betriebstemperatur	-20°C - +50°C
Breite	30,00 mm	Gehäusetemperatur	90 °C
Höhe	17,00 mm	max. Menge Sicherungsautomaten	B10A=5, B16A=9, C10A=12, C16A=19
Durchmesser	0,00 mm	max. Einschaltstrom	30A/300µs
Gewicht	152 g	kapazitive Last	451,2nF

Article No.: 862094

Power supply unit, LONG-FLAT, CV, LT-60-24












IP20 CE

Electrical Characteristics

Operating mode	constant voltage	Input voltage	220-240V AC/50-60Hz
Power	60,00 W	Power factor	0,95
Output voltage	24V DC	Connection possibility	clamp
Output current	0-2500 mA		


Product features

	Protection class II		Overvoltage protection
SELV	Low voltage protection		Lamp control gear 110
	Short circuit protection		Suitable for furniture installation
	Overload protection	ErP	Standby-power consumption < 0,5 W
	Overheating protection	LVD	Safety according to EN 61347
	Safety transformer	EMC	Interference suppression + immunity according to EN 55015 + EN 61547
	not dimmable	EMC	Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

Article No.: 862094

Power supply unit, LONG-FLAT, CV, LT-60-24

**Dimensions & Weight****Absolute maximum ratings**

Length	305,00 mm	Operating temperature	-20°C - +50°C
Width	30,00 mm	Case temperature	90 °C
Height	17,00 mm	max. amount of circuit breakers	B10A=5, B16A=9, C10A=12, C16A=19
Diameter	0,00 mm	max. inrush current	30A/300µs
Product weight	152 g	capacitive load	451,2nF