

Artikel Nr.: 862235

Netzgerät, OCTO, DIM, CC, RSM-12-350T/12W












IP65 CE

Elektrische Daten

Betriebsart	stromkonstant	Eingangsspannung	220-240V AC/50-60Hz
Leistung	6,30-12,00 W	Leistungsfaktor	0,94
Ausgangsspannung	18-37V DC	Anschlußmöglichkeit	offene Kabel
Ausgangsstrom	350 mA		


Produkteigenschaften

	Schutzklasse II		Überspannungsschutz
SELV	Schutzkleinspannung		Lampenbetriebsgerät 110
	Kurzschlußfest		Möbeleinbau geeignet
	Überlastschutz	ErP	Standby-Stromverbrauch < 0,5 W
	Übertemperaturschutz	LVD	Sicherheit nach EN 61347
	Sicherheitstrafo	EMC	Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
	dimmbar - Phasenabschnitt	EMC	Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

Artikel Nr.: 862235

Netzgerät, OCTO, DIM, CC, RSM-12-350T/12W



Abmessungen und Gewicht

Grenzwerte

Länge	50,00 mm	Betriebstemperatur	-20°C - +50°C
Breite	48,00 mm	Gehäusetemperatur	0 °C
Höhe	24,00 mm	max. Menge Sicherungsautomaten	B10A=125, B16A=200, C10A=125, C16A=200
Durchmesser	0,00 mm	max. Einschaltstrom	5A/100µs
Gewicht	g	kapazitive Last	190uf

Article No.: 862235

Power supply unit, OCTO, DIM, CC, RSM-12-350T/12W












IP65 CE

Electrical Characteristics

Operating mode	constant current	Input voltage	220-240V AC/50-60Hz
Power	6,30-12,00 W	Power factor	0,94
Output voltage	18-37V DC	Connection possibility	wire with open ends
Output current	350 mA		


Product features

	Protection class II		Overvoltage protection
SELV	Low voltage protection		Lamp control gear 110
	Short circuit protection		Suitable for furniture installation
	Overload protection	ErP	Standby-power consumption < 0,5 W
	Overheating protection	LVD	Safety according to EN 61347
	Safety transformer	EMC	Interference suppression + immunity according to EN 55015 + EN 61547
	dimnable - trailing edge	EMC	Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

Article No.: 862235

Power supply unit, OCTO, DIM, CC, RSM-12-350T/12W

**Dimensions & Weight****Absolute maximum ratings**

Length	50,00 mm	Operating temperature	-20°C - +50°C
Width	48,00 mm	Case temperature	0 °C
Height	24,00 mm	max. amount of circuit breakers	B10A=125, B16A=200, C10A=125, C16A=200
Diameter	0,00 mm	max. inrush current	5A/100µs
Product weight	g	capacitive load	190uf